



SL-105

HOIST MODEL

ENGINEERED FOR THE CLASS 4-5 LIGHT-DUTY TRUCK MARKET

SL-105

10,500 lb. Capacity



FEATURES INCLUDE

- ➡ 10,500 lb. Lift/Dump Capacity
- ➡ Fixed 35-5/8" Hook Height
- ➡ Potential Body Lengths: 10' - 13'
- ➡ Slide-through Body Lock or Optional Patented Universal Body Lock
- ➡ Powder Coat Finish
- ➡ Dual Lift/Dump Cylinders
- ➡ Dual Rear Pivot Section
- ➡ 5-Year Limited Warranty



SL-105

SPECIFICATIONS

MODEL		SL-105
MODEL DESCRIPTION	LIFT/DUMP CAPACITY (INCLUDING CONTAINER)	10,500 lb
	DUMP ANGLE	58°
	HOIST WEIGHT**	FIXED 1,570 lb
		ADJ. N/A
GENERAL DIMENSIONS	HOOK TO REAR ROLLER	116.00"
	HOOK HEIGHT	FIXED 35.63"
		ADJ. N/A
	HOIST HEIGHT	5.5"
	HOIST CG	58.1"
	OPTIMUM BODY LENGTHS	10' - 12'
	POTENTIAL BODY LENGTHS*	10' - 13'
HYDRAULIC SYSTEMS	BODY LONGSILL WIDTH*	41.63"
	HYDRAULIC PUMP TYPE (CID)	Gear (1.86)
	FLOW @ PUMP RPM*	7.2 GPM @ 1,000 RPM
	RELIEF PRESSURE	3,250 PSI
LIFT CYLINDER	HYDRAULIC RESERVOIR	15 gal
	QUANTITY	2
	BORE	Ø 4"
JIB CYLINDER	STROKE	38"
	QUANTITY	1
	BORE	Ø 2.5"
TRUCK SPECS (RECOMMENDED)	STROKE	24"
	GVW RANGE*	16,000 lb - 19,500 lb
	CAB-AXLE DIM.* (SINGLE AXLE)	84" - 96"
	CAB-TRUNNION DIM. (TANDEM AXLE)	N/A
	CLEAR FRAME RAIL*	130"
PTO SPECS (RECOMMENDED)	FRAME HEIGHT	up to 40"
	PUMP MOUNT*	Direct Mount SAE A, 2 Bolt
	TORQUE REQUIRED	80 ft-lbf

*See All-Model Specifications literature for further information.

**Weight includes base hoist with installation kit and cylinder oil.