



SL-105

HOIST MODEL

ENGINEERED FOR THE CLASS 4-5 LIGHT-DUTY TRUCK MARKET

SL-105

10,500 lb. Capacity



FEATURES INCLUDE

- ➡ 10,500 lb. Lift/Dump Capacity
- ➡ Fixed 35-5/8" Hook Height
- ➡ Potential Body Lengths: 10' - 13'
- ➡ Slide-through Body Lock or Optional Patented Universal Body Lock
- ➡ Powder Coat Finish
- ➡ Dual Lift/Dump Cylinders
- ➡ Dual Rear Pivot Section
- ➡ 5-Year Limited Warranty



SL-105

SPECIFICATIONS

MODEL			SL-105
MODEL DESCRIPTION	LIFT/DUMP CAPACITY (INCLUDING CONTAINER)		10,500 lb
	DUMP ANGLE		58°
	HOIST WEIGHT**	FIXED	1,570 lb
		ADJ.	N/A
GENERAL DIMENSIONS	HOOK TO REAR ROLLER		116.00"
	HOOK HEIGHT	FIXED	35.63"
		ADJ.	N/A
	HOIST HEIGHT		5.5"
	HOIST CG		58.1"
	OPTIMUM BODY LENGTHS		10' - 12'
	POTENTIAL BODY LENGTHS*		10' - 13'
HYDRAULIC SYSTEMS	BODY LONGSILL WIDTH*		41.63"
	HYDRAULIC PUMP TYPE (CID)		Gear (1.86)
	FLOW @ PUMP RPM*		7.2 GPM @ 1,000 RPM
	RELIEF PRESSURE		3,250 PSI
LIFT CYLINDER	HYDRAULIC RESERVOIR		15 gal
	QUANTITY		2
	BORE		Ø 4"
JIB CYLINDER	STROKE		38"
	QUANTITY		1
	BORE		Ø 2.5"
TRUCK SPECS (RECOMMENDED)	STROKE		24"
	GVW RANGE*		16,000 lb - 19,000 lb
	CAB-AXLE DIM.* (SINGLE AXLE)		84" - 96"
	CAB-TRUNNION DIM. (TANDEM AXLE)		N/A
PTO SPECS (RECOMMENDED)	CLEAR FRAME RAIL*		130"
	FRAME HEIGHT		up to 40"
	PUMP MOUNT*		Direct Mount SAE A, 2 Bolt
PTO SPECS (RECOMMENDED)	TORQUE REQUIRED		80 ft-lbf

*See All-Model Specifications literature for further information.

**Weight includes base hoist with installation kit and cylinder oil.



📍 1800 Broadway Avenue, Des Moines, IA 50313-2644

☎ 515-266-3042 📞 888-767-8000 🌐 www.swaploader.com

© 2025 Swaploader, USA. All rights reserved. SWL-F-SL-105 07.09.25