



SL-650

HOIST MODEL

ENGINEERED FOR THE CLASS 8 HEAVY-DUTY TRUCK MARKET

SL-650

65,000 lb. Capacity



FEATURES INCLUDE

- ↔ 65,000 lb. Lift/Dump Capacity
- ↔ Fixed 61-3/4" Hook Height
- ↔ Potential Body Lengths: 17' - 24'
- ↔ Slide-through Body Lock or Optional Patented Universal Body Lock
- ↔ Powder Coat Finish
- ↔ Dual Lift/Dump Cylinders
- ↔ Dual Rear Pivot Section
- ↔ 5-Year Limited Warranty



SL-650

SPECIFICATIONS

MODEL		SL-650
MODEL DESCRIPTION	LIFT/DUMP CAPACITY (INCLUDING CONTAINER)	65,000 lb
	DUMP ANGLE	54°
	HOIST WEIGHT**	8,190 lb N/A
GENERAL DIMENSIONS	HOOK TO REAR ROLLER	226.50"
	HOOK HEIGHT	61.75" N/A
	HOIST HEIGHT	13"
	HOIST CG	125.0"
	OPTIMUM BODY LENGTHS	20' - 22'
	POTENTIAL BODY LENGTHS*	17' - 24'
	BODY LONGSILL WIDTH*	40.50" / 41.63"
HYDRAULIC SYSTEMS	HYDRAULIC PUMP TYPE (CID)	Gear (4.46)
	FLOW @ PUMP RPM*	26.0 GPM @ 1,500 RPM
	RELIEF PRESSURE	3,500 PSI
	HYDRAULIC RESERVOIR	30 gal
LIFT CYLINDER	QUANTITY	2
	BORE	Ø 7.5"
	STROKE	82"
JIB CYLINDER	QUANTITY	1
	BORE	Ø 4.5"
	STROKE	52"
TRUCK SPECS (RECOMMENDED)	GVW RANGE*	55,000 lb or Greater
	CAB-AXLE DIM.* (SINGLE AXLE)	N/A
	CAB-TRUNNION DIM. (TANDEM AXLE)	183" - 195"
	CLEAR FRAME RAIL*	252"
	FRAME HEIGHT	up to 453"
PTO SPECS (RECOMMENDED)	PUMP MOUNT*	Direct Mount SAE B, 4 Bolt
	TORQUE REQUIRED	230 ft-lbf

*See All-Model Specifications literature for further information.

**Weight includes base hoist with installation kit and cylinder oil.