



SL-75

HOIST MODEL

ENGINEERED FOR THE CLASS 4 LIGHT-DUTY TRUCK MARKET

SL-75

7,500 lb. Capacity



FEATURES INCLUDE

- ↔ 7,500 lb. Lift/Dump Capacity
- ↔ Fixed 35-5/8" Hook Height
- ↔ Potential Body Lengths: 9' - 13'
- ↔ Slide-through Body Lock or Optional Patented Universal Body Lock
- ↔ Powder Coat Finish
- ↔ Dual Jib Cylinders
- ↔ Dual Rear Pivot Section
- ↔ 5-Year Limited Warranty



SL-75

SPECIFICATIONS

MODEL			SL-75
MODEL DESCRIPTION	LIFT/DUMP CAPACITY (INCLUDING CONTAINER)		7,500 lb
	DUMP ANGLE		56°
	HOIST WEIGHT**	FIXED	1,290 lb
		ADJ.	N/A
GENERAL DIMENSIONS	HOOK TO REAR ROLLER		114.38"
	HOOK HEIGHT	FIXED	35.63"
		ADJ.	N/A
	HOIST HEIGHT		5.25"
	HOIST CG		59.7"
	OPTIMUM BODY LENGTHS		10' - 12'
	POTENTIAL BODY LENGTHS*		9' - 13'
HYDRAULIC SYSTEMS	BODY LONGSILL WIDTH*		41.63" / 39.00"
	HYDRAULIC PUMP TYPE (CID)		Gear (0.85)
	FLOW @ PUMP RPM*		3.1 GPM @ 1,000 RPM
	RELIEF PRESSURE		3,250 PSI
	HYDRAULIC RESERVOIR		7 gal
LIFT CYLINDER	QUANTITY		1
	BORE		Ø 4"
	STROKE		38"
JIB CYLINDER	QUANTITY		2
	BORE		Ø 1.5"
	STROKE		20"
TRUCK SPECS (RECOMMENDED)	GVW RANGE*		14,000 lb - 16,000 lb
	CAB-AXLE DIM.* (SINGLE AXLE)		84" - 96"
	CAB-TRUNNION DIM. (TANDEM AXLE)		N/A
	CLEAR FRAME RAIL*		126"
	FRAME HEIGHT		up to 38"
PTO SPECS (RECOMMENDED)	PUMP MOUNT*		Direct Mount SAE A, 2 Bolt
	TORQUE REQUIRED		40 ft-lbf

*See All-Model Specifications literature for further information.

**Weight includes base hoist with installation kit and cylinder oil.



1800 Broadway Avenue, Des Moines, IA 50313-2644

515-266-3042 888-767-8000 www.swaploader.com

© 2025 Swaploader, USA. All rights reserved. SWL-F-SL-75 07.09.25