



# SL-112

HOIST MODEL

## ENGINEERED FOR THE CLASS 4-6 LIGHT-DUTY TRUCK MARKET

### SL-112

12,000 lb. Capacity



### FEATURES INCLUDE

- ↔ 12,000 lb. Lift/Dump Capacity
- ↔ Adjustable Jib with 35-5/8" or 53-7/8" Hook Heights
- ↔ Potential Body Lengths: 10' - 15'
- ↔ Slide-through Body Lock or Optional Patented Universal Body Lock
- ↔ Dual Retention Jib Adjustment Pin
- ↔ Adjustable Puck-Style Wear Pads - No Steel on Steel Contact
- ↔ Powder Coat Finish
- ↔ Dual Lift/Dump Cylinders
- ↔ Dual Rear Pivot Section
- ↔ 5-Year Limited Warranty



# SL-112

## SPECIFICATIONS

| MODEL                     |                                          |               | SL-112                 |
|---------------------------|------------------------------------------|---------------|------------------------|
| MODEL DESCRIPTION         | LIFT/DUMP CAPACITY (INCLUDING CONTAINER) |               | 12,000 lb              |
|                           | DUMP ANGLE                               |               | 55°                    |
|                           | HOIST WEIGHT**                           | FIXED<br>ADJ. | N/A<br>2,060 lb        |
| GENERAL DIMENSIONS        | HOOK TO REAR ROLLER                      |               | 135.38"                |
|                           | HOOK HEIGHT                              | FIXED<br>ADJ. | N/A<br>35.63" / 53.88" |
|                           | HOIST HEIGHT                             |               | 6.625"                 |
|                           | HOIST CG                                 |               | 68.8"                  |
|                           | OPTIMUM BODY LENGTHS                     |               | 12' - 14'              |
|                           | POTENTIAL BODY LENGTHS*                  |               | 10' - 15'              |
| HYDRAULIC SYSTEMS         | BODY LONGSILL WIDTH*                     |               | 41.63" / 40.50"        |
|                           | FLOW (RECOMMENDED)                       |               | 7.2 GPM                |
|                           | RELIEF PRESSURE                          |               | 3,250 PSI              |
| LIFT CYLINDER             | HYDRAULIC RESERVOIR                      |               | 15 gal                 |
|                           | QUANTITY                                 |               | 2                      |
|                           | BORE                                     |               | Ø 4.5"                 |
| JIB CYLINDER              | STROKE                                   |               | 44"                    |
|                           | QUANTITY                                 |               | 1                      |
|                           | BORE                                     |               | Ø 2.5"                 |
| TRUCK SPECS (RECOMMENDED) | STROKE                                   |               | 28"                    |
|                           | GVWR RANGE*                              |               | 16,000 lb - 23,000 lb  |
|                           | CAB-AXLE DIM.* (SINGLE AXLE)             |               | 108" - 120"            |
|                           | CAB-TRUNNION DIM. (TANDEM AXLE)          |               | N/A                    |
|                           | CLEAR FRAME RAIL*                        |               | 152"                   |
| FRAME HEIGHT              |                                          | up to 38"     |                        |

\*See All-Model Specifications literature for further information.

\*\*Weight includes base hoist with installation kit and cylinder oil.



📍 1800 NE Broadway Avenue, Des Moines, IA 50313-2644  
 ☎ 515-266-3042 📞 888-767-8000 🌐 [www.swaploader.com](http://www.swaploader.com)

© 2025 Swaploader, USA. All rights reserved. SWL-F-SL-112 10.15.25