



SL-110/SL-112

HOIST MODEL

ENGINEERED FOR THE CLASS 4-6 LIGHT-DUTY TRUCK MARKET

SL-110

12,000 lb. Capacity

SL-112

12,000 lb. Capacity



FEATURES INCLUDE

- ↔ 12,000 lb. Lift/Dump Capacity
- ↔ Adjustable Jib with 35-5/8" or 53-7/8" Hook Heights
- ↔ Potential Body Lengths:
 - SL-110 9' - 13'
 - SL-112 10' - 15'
- ↔ Slide-through Body Lock or Patented U-Lock
- ↔ Dual Retention Jib Lock Pin
- ↔ Adjustable Puck-Style Wear Pads
- ↔ Dual Lift/Dump Cylinders
- ↔ Dual Rear Pivot Section
- ↔ Powder Coat Finish
- ↔ 5-Year Limited Warranty



SL-110/SL-112

SPECIFICATIONS

MODEL		SL-110	SL-112
MODEL DESCRIPTION	LIFT/DUMP CAPACITY (INCLUDING CONTAINER)	12,000 lb	12,000 lb
	DUMP ANGLE	58°	55°
	HOIST WEIGHT**	N/A	N/A
GENERAL DIMENSIONS	FIXED	N/A	N/A
	ADJ.	1,810 lb	2,060 lb
	HOOK TO REAR ROLLER	111.00"	135.38"
	HOOK HEIGHT	N/A	N/A
	ADJ.	35.63" / 53.88"	35.63" / 53.88"
	HOIST HEIGHT	6.625"	6.625"
	HOIST CG	54.9"	68.8"
HYDRAULIC SYSTEMS	OPTIMUM BODY LENGTHS	10' - 12'	12' - 14'
	POTENTIAL BODY LENGTHS*	9' - 13'	10' - 15'
	BODY LONGSILL WIDTH*	41.63" / 40.50"	41.63" / 40.50"
LIFT CYLINDER	FLOW (RECOMMENDED)	7.2 GPM	7.2 GPM
	RELIEF PRESSURE	3,250 PSI	3,250 PSI
	HYDRAULIC RESERVOIR	15 gal	15 gal
JIB CYLINDER	QUANTITY	2	2
	BORE	Ø 4"	Ø 4.5"
	STROKE	38"	44"
TRUCK SPECS (RECOMMENDED)	QUANTITY	1	1
	BORE	Ø 2.5"	Ø 2.5"
	STROKE	24"	28"
	GVWR RANGE*	16,000 lb - 23,000 lb	16,000 lb - 23,000 lb
	CAB-AXLE DIM.* (SINGLE AXLE)	84" - 96"	108" - 120"
	CAB-TRUNNION DIM. (TANDEM AXLE)	N/A	N/A
	CLEAR FRAME RAIL*	129"	152"
	FRAME HEIGHT	up to 36"	up to 38"

*See All-Model Specifications literature for further information.

**Weight includes base hoist with installation kit and cylinder oil.



1800 NE Broadway Avenue, Des Moines, IA 50313-2644
 515-266-3042 888-767-8000 www.swaploader.com

© 2026 Swaploader U.S.A. Ltd. All rights reserved. SWL-F-SL-110/SL-112 02.03.26