



SL-240

HOIST MODEL

ENGINEERED FOR THE CLASS 6-7 MEDIUM-DUTY TRUCK MARKET

SL-240

24,000 lb. Capacity



FEATURES INCLUDE

- ↔ 24,000 lb. Lift/Dump Capacity
- ↔ Fixed 53-7/8" Hook Height or Adjustable Jib
Option with 53-7/8" or 61-3/4" Hook Heights
- ↔ Potential Body Lengths: 12' - 18'
- ↔ Slide-through Body Lock or
Optional Patented Universal Body Lock
- ↔ Powder Coat Finish
- ↔ Dual Lift/Dump Cylinders
- ↔ Dual Rear Pivot Section
- ↔ 5-Year Limited Warranty



SL-240

SPECIFICATIONS

MODEL		SL-240	
MODEL DESCRIPTION	LIFT/DUMP CAPACITY (INCLUDING CONTAINER)	24,000 lb	
	DUMP ANGLE	53°	
	HOIST WEIGHT**	FIXED	3,920 lb
ADJ.		4,150 lb	
GENERAL DIMENSIONS	HOOK TO REAR ROLLER	159.81"	
	HOOK HEIGHT	FIXED	53.88"
		ADJ.	53.88" / 61.75"
	HOIST HEIGHT	9"	
	HOIST CG	88.0"	
	OPTIMUM BODY LENGTHS	14' - 16'	
	POTENTIAL BODY LENGTHS*	12' - 18'	
BODY LONGSILL WIDTH*	41.63" / 40.50"		
HYDRAULIC SYSTEMS	FLOW (RECOMMENDED)	17.4 GPM	
	RELIEF PRESSURE	2,800 PSI	
	HYDRAULIC RESERVOIR	25 gal	
LIFT CYLINDER	QUANTITY	2	
	BORE	Ø 6"	
	STROKE	54"	
JIB CYLINDER	QUANTITY	1	
	BORE	Ø 3.5"	
	STROKE	30"	
TRUCK SPECS (RECOMMENDED)	GVWR RANGE*	25,000 lb - 35,000 lb	
	CAB-AXLE DIM.* (SINGLE AXLE)	130" - 144"	
	CAB-TRUNNION DIM. (TANDEM AXLE)	118" - 130"	
	CLEAR FRAME RAIL*	186"	
	FRAME HEIGHT	up to 43"	

*See All-Model Specifications literature for further information.

**Weight includes base hoist with installation kit and cylinder oil.



📍 1800 Broadway Avenue, Des Moines, IA 50313-2644

☎ 515-266-3042 📞 888-767-8000 🌐 www.swaploader.com

© 2026 Swaploader U.S.A. Ltd. All rights reserved. SWL-036-SL-240 04.10.26