



# SL-75

HOIST MODEL

## ENGINEERED FOR THE CLASS 4 LIGHT-DUTY TRUCK MARKET

**SL-75**  
7,500 lb. Capacity



### FEATURES INCLUDE

- ↔ 7,500 lb. Lift/Dump Capacity
- ↔ Fixed 35-5/8" Hook Height
- ↔ Potential Body Lengths: 9' - 13'
- ↔ Slide-through Body Lock or Optional Patented Universal Body Lock
- ↔ Powder Coat Finish
- ↔ Dual Jib Cylinders
- ↔ Dual Rear Pivot Section
- ↔ 5-Year Limited Warranty





# SL-75

## SPECIFICATIONS

MODEL		SL-75	
MODEL DESCRIPTION	LIFT/DUMP CAPACITY (INCLUDING CONTAINER)	7,500 lb	
	DUMP ANGLE	56°	
	HOIST WEIGHT**	FIXED	1,290 lb
ADJ.		—	
GENERAL DIMENSIONS	HOOK TO REAR ROLLER	114.38"	
	HOOK HEIGHT	FIXED	35.63"
		ADJ.	—
	HOIST HEIGHT	5.25"	
	HOIST CG	59.7"	
	<b>OPTIMUM BODY LENGTHS</b>	<b>10' - 12'</b>	
	POTENTIAL BODY LENGTHS*	9' - 13'	
BODY LONGSILL WIDTH*	41.63" / 39.00"		
HYDRAULIC SYSTEMS	FLOW (RECOMMENDED)	3.1 GPM	
	RELIEF PRESSURE	3,250 PSI	
	HYDRAULIC RESERVOIR	7 gal	
LIFT CYLINDER	QUANTITY	1	
	BORE	Ø 4"	
	STROKE	38"	
JIB CYLINDER	QUANTITY	2	
	BORE	Ø 1.5"	
	STROKE	20"	
TRUCK SPECS (RECOMMENDED)	GVWR RANGE*	14,000 lb - 16,000 lb	
	CAB-AXLE DIM.* (SINGLE AXLE)	84" - 96"	
	CAB-TRUNNION DIM. (TANDEM AXLE)	—	
	CLEAR FRAME RAIL*	126"	
	FRAME HEIGHT	up to 38"	

\*See All-Model Specifications literature for further information.

\*\*Weight includes base hoist with installation kit and cylinder oil.



1800 Broadway Avenue, Des Moines, IA 50313-2644

515-266-3042 888-767-8000 www.swaploader.com

© 2026 Swaploader U.S.A. Ltd. All rights reserved. SWL-937-SL-75 04.10.26