



SL-220/SL-222

HOIST MODELS

ENGINEERED FOR THE CLASS 6-7 MEDIUM-DUTY TRUCK MARKET

SL-220

22,000 lb. Capacity

SL-222

22,000 lb. Capacity



FEATURES INCLUDE

- ↪ 22,000 lb. Lift/Dump Capacity
- ↪ Fixed 53-7/8" Hook Height or Adjustable Jib Option with 53-7/8" or 61-3/4" Hook Heights
- ↪ Potential Body Lengths
 - SL-220 14' - 22'
 - SL-222 14' - 20'
- ↪ Slide-through Body Lock or Optional Patented Universal Body Lock
- ↪ Powder Coat Finish
- ↪ Dual Lift/Dump Cylinders
- ↪ Dual Rear Pivot Section
- ↪ 5-Year Limited Warranty



SL-220/SL-222

SPECIFICATIONS

MODEL		SL-220	SL-222	
MODEL DESCRIPTION	LIFT/DUMP CAPACITY (INCLUDING CONTAINER)	22,000 lb	22,000 lb	
	DUMP ANGLE	53°	53°	
	HOIST WEIGHT**	FIXED	4,080 lb	4,110 lb
ADJ.		4,270 lb	4,330 lb	
GENERAL DIMENSIONS	HOOK TO REAR ROLLER	193.81"	179.81"	
	HOOK HEIGHT	FIXED	53.88"	53.88"
		ADJ.	53.88" / 61.75"	53.88" / 61.75"
	HOIST HEIGHT	9"	9"	
	HOIST CG	97.8"	95.2"	
	OPTIMUM BODY LENGTHS	18' - 20'	16' - 18'	
	POTENTIAL BODY LENGTHS*	14' - 22'	14' - 20'	
BODY LONGSILL WIDTH*	41.63" / 40.50"	41.63" / 40.50"		
HYDRAULIC SYSTEMS	FLOW (RECOMMENDED)	174 GPM	174 GPM	
	RELIEF PRESSURE	2,800 PSI	2,800 PSI	
	HYDRAULIC RESERVOIR	25 gal	25 gal	
LIFT CYLINDER	QUANTITY	2	2	
	BORE	Ø 6"	Ø 6"	
	STROKE	54"	54"	
JIB CYLINDER	QUANTITY	1	1	
	BORE	Ø 3.5"	Ø 3.5"	
	STROKE	48"	34"	
TRUCK SPECS (RECOMMENDED)	GVWR RANGE*	25,000 lb - 35,000 lb	25,000 lb - 35,000 lb	
	CAB-AXLE DIM.* (SINGLE AXLE)	156" - 174"	142" - 160"	
	CAB-TRUNNION DIM. (TANDEM AXLE)	148" - 160"	134" - 146"	
	CLEAR FRAME RAIL*	220"	206"	
	FRAME HEIGHT	up to 43"	up to 43"	

*See All-Model Specifications literature for further information.

**Weight includes base hoist with installation kit and cylinder oil.



1800 Broadway Avenue, Des Moines, IA 50313-2644

515-266-3042 888-767-8000 www.swaploader.com

© 2026 Swaploader U.S.A. Ltd. All rights reserved. SWL-983-SL-220/SL-222 04.10.26