



SL-330/SL-400

HOIST MODELS

ENGINEERED FOR THE CLASS 7-8 MEDIUM-HEAVY DUTY TRUCK MARKET

SL-330

33,000 lb. Capacity

SL-400

40,000 lb. Capacity



FEATURES INCLUDE

- ↪ 33,000 - 40,000 lb. Lift/Dump Capacity
- ↪ Fixed 61-3/4" Hook Height or Adjustable Jib
Option with 61-3/4" or 53-7/8" Hook Heights
- ↪ Potential Body Lengths
 - SL-330 12' - 18'
 - SL-400 12' - 18'
- ↪ Polished Nitrided Cylinder Rod
- ↪ Slide-through Body Lock or
Optional Patented Universal Body Lock
- ↪ Powder Coat Finish
- ↪ Dual Lift/Dump Cylinders
- ↪ Dual Rear Pivot Section
- ↪ 5-Year Limited Warranty





SL-330/SL-400

SPECIFICATIONS

MODEL		SL-330	SL-400	
MODEL DESCRIPTION	LIFT/DUMP CAPACITY (INCLUDING CONTAINER)	33,000 lb	40,000 lb	
	DUMP ANGLE	58°	58°	
	HOIST WEIGHT**	FIXED	5,090 lb	5,240 lb
ADJ.		5,250 lb	5,410 lb	
GENERAL DIMENSIONS	HOOK TO REAR ROLLER	167.50"	167.50"	
	HOOK HEIGHT	FIXED	61.75"	61.75"
		ADJ.	61.75" / 53.88"	61.75" / 53.88"
	HOIST HEIGHT	11"	11"	
	HOIST CG	88.8"	88.8"	
	OPTIMUM BODY LENGTHS	14' - 16'	14' - 16'	
	POTENTIAL BODY LENGTHS*	12' - 18'	12' - 18'	
BODY LONGSILL WIDTH*	40.50" / 41.63"	40.50" / 41.63"		
HYDRAULIC SYSTEMS	FLOW (RECOMMENDED)	22.3 GPM	22.3 GPM	
	RELIEF PRESSURE	3,500 PSI	3,500 PSI	
	HYDRAULIC RESERVOIR	30 gal	30 gal	
LIFT CYLINDER	QUANTITY	2	2	
	BORE	Ø 5.5"	Ø 6"	
	STROKE	60"	60"	
JIB CYLINDER	QUANTITY	1	1	
	BORE	Ø 4"	Ø 4"	
	STROKE	38"	38"	
TRUCK SPECS (RECOMMENDED)	GVWR RANGE*	33,000 lb or greater	45,000 lb or greater	
	CAB-AXLE DIM.* (SINGLE AXLE)	142" - 156"	—	
	CAB-TRUNNION DIM. (TANDEM AXLE)	124" - 136"	124" - 136"	
	CLEAR FRAME RAIL*	195"	195"	
	FRAME HEIGHT	up to 43"	up to 43"	

*See All-Model Specifications literature for further information.

**Weight includes base hoist with installation kit and cylinder oil.



📍 1800 Broadway Avenue, Des Moines, IA 50313-2644

☎ 515-266-3042 📞 888-767-8000 🌐 www.swaploader.com

© 2026 Swaploader U.S.A. Ltd. All rights reserved. SWL-984-SL-330/SL-400 04.10.26