



SL-650

HOIST MODEL

ENGINEERED FOR THE CLASS 8 HEAVY-DUTY TRUCK MARKET

SL-650

65,000 lb. Capacity



FEATURES INCLUDE

- ↻ 65,000 lb. Lift/Dump Capacity
- ↻ Fixed 61-3/4" Hook Height
- ↻ Potential Body Lengths: 17' - 24'
- ↻ Slide-through Body Lock or Optional Patented Universal Body Lock
- ↻ Powder Coat Finish
- ↻ Dual Lift/Dump Cylinders
- ↻ Dual Rear Pivot Section
- ↻ 5-Year Limited Warranty





SL-650 SPECIFICATIONS

MODEL		SL-650	
MODEL DESCRIPTION	LIFT/DUMP CAPACITY (INCLUDING CONTAINER)	65,000 lb	
	DUMP ANGLE	54°	
	HOIST WEIGHT**	FIXED	8,190 lb
ADJ.		—	
GENERAL DIMENSIONS	HOOK TO REAR ROLLER	226.50"	
	HOOK HEIGHT	FIXED	61.75"
		ADJ.	—
	HOIST HEIGHT	13"	
	HOIST CG	125.0"	
	OPTIMUM BODY LENGTHS	20' - 22'	
POTENTIAL BODY LENGTHS*	17' - 24'		
BODY LONGSILL WIDTH*	40.50"/41.63"		
HYDRAULIC SYSTEMS	FLOW (RECOMMENDED)	26.0 GPM	
	RELIEF PRESSURE	3,500 PSI	
	HYDRAULIC RESERVOIR	30 gal	
LIFT CYLINDER	QUANTITY	2	
	BORE	Ø 7.5"	
	STROKE	82"	
JIB CYLINDER	QUANTITY	1	
	BORE	Ø 4.5"	
	STROKE	52"	
TRUCK SPECS (RECOMMENDED)	GVWR RANGE*	55,000 lb or greater	
	CAB-AXLE DIM.* (SINGLE AXLE)	—	
	CAB-TRUNNION DIM. (TANDEM AXLE)	183"-195"	
	CLEAR FRAME RAIL*	252"	
	FRAME HEIGHT	up to 45"	

*See All-Model Specifications literature for further information.

**Weight includes base hoist with installation kit and cylinder oil.



1800 Broadway Avenue, Des Moines, IA 50313-2644

515-266-3042 888-767-8000 www.swaploader.com

© 2026 Swaploader U.S.A. Ltd. All rights reserved. SWL-988-SL-650 04.10.26