



An EFCO Company

# SWAPLOADER®

"Hooked on Quality" U.S.A. LTD.

## X SERIES LINEUP



NEWLY OPTIMIZED FOR THE WASTE, CONSTRUCTION,  
AND AGRICULTURE INDUSTRIES



**SL-418X**

40,000 lb capacity

**SL-518X**

50,000 lb capacity

**SL-520X**

50,000 lb capacity

### FEATURES INCLUDE

- Fixed 61-3/4" hook height or adjustable jib option from 53-7/8" to 61-3/4" hook heights
- Optimal Body Lengths
  - SL-418X 18' - 20'
  - SL-518X 18' - 20'
  - SL-520X 20' - 22'
- New secure lock pin design
- Easily serviceable wear pads
- Lighter weight design/increased payload
- Reduced payload height
- Powder coat finish
- Optional Dual Rear Roller with new lightweight design
- Optional Universal or Outside Hydraulic Body Lock

1800 NE Broadway Avenue, Des Moines, IA 50313 | email: sales@swaploader.net | toll free: 888.767.8000 | phone: 515.266.3042

MADE IN **USA**★

[www.swaploader.com](http://www.swaploader.com)





An EFCO Company

# SWAPLOADER®

"Hooked on Quality"

U.S.A. LTD.

## X SERIES SPECIFICATIONS

MODEL	SL-418X	SL-518X	SL-520X	
<b>MODEL DESCRIPTION</b>	DUMP CAPACITY (INCLUDING CONTAINER)	40,000 lb	50,000 lb	50,000 lb
	DUMP ANGLE	58°	58°	60°
	LIFT CAPACITY (INCLUDING CONTAINER)	40,000 lb	50,000 lb	50,000 lb
	HOIST WEIGHT**	FIXED: 5,900 lb ADJ.: 6,040 lb	5,900 lb 6,040 lb	6,185 lb 6,325 lb
<b>GENERAL DIMENSIONS (SEE DIAGRAM)</b>	HOOK TO REAR ROLLER (DIM. A)	201.00"	201.00"	222.75"
	HOOK HEIGHT (DIM. B)	FIXED: 61.75" ADJ.: 61.75" / 53.88"	61.75" 61.75" / 53.88"	61.75" 61.75" / 53.88"
	HOIST HEIGHT (DIM. C)	11.5"	11.5"	11.5"
	HOIST CG (DIM. D)	105.5"	105.5"	115.0"
	OPTIMUM BODY LENGTHS (DIM. E)	18' - 20'	18' - 20'	20' - 22'
	POTENTIAL BODY LENGTHS* (DIM. E)	14' - 22'	14' - 22'	17' - 24'
	BODY LONGSILL WIDTH*	40.50" / 41.63"	40.50" / 41.63"	40.50" / 41.63"
<b>HYDRAULIC SYSTEMS</b>	HYDRAULIC PUMP TYPE (CID)	Bent Axis Piston (3.84)	Bent Axis Piston (3.84)	Bent Axis Piston (3.84)
	FLOW @ PUMP RPM*	21.0 GPM @ 1,300 RPM	21.0 GPM @ 1,300 RPM	21 GPM @ 1,300 RPM
	RELIEF PRESSURE	3,850 PSI	4,650 PSI	4,650 PSI
	HYDRAULIC RESERVOIR	25 gal	25 gal	25 gal
<b>LIFT CYLINDER</b>	QUANTITY	2	2	2
	BORE	Ø 6"	Ø 6"	Ø 6"
	STROKE	78.75"	78.75"	85.25"
<b>JIB CYLINDER</b>	QUANTITY	1	1	1
	BORE	Ø 4"	Ø 4"	Ø 4"
	STROKE	48"	48"	52"
<b>TRUCK SPECS (RECOMMENDED)</b>	GVW RANGE*	45,000 lb or greater	50,000 lb or greater	50,000 lb or greater
	CAB-AXLE DIM.* (SINGLE AXLE)	N/A	N/A	N/A
	CAB-TRUNNION DIM. (TANDEM AXLE)	158" - 170"	158" - 170"	176" - 190"
	CLEAR FRAME RAIL*	229"	229"	246"
	FRAME HEIGHT	up to 45"	up to 45"	up to 45"
<b>PTO SPECS (RECOMMENDED)</b>	PUMP MOUNT*	Direct Mount SAE B-B, 4 Bolt Spline Shaft 1" 15T 16/32	Direct Mount SAE B-B, 4 Bolt Spline Shaft 1" 15T 16/32	Direct Mount SAE B-B, 4 Bolt Spline Shaft 1" 15T 16/32
	TORQUE REQUIRED	250 ft-lbf	250 ft-lbf	250 ft-lbf

\*See All-Model Specifications literature for further information  
 \*\*Weight includes base hoist with installation kit and cylinder oil